

STRUCTURE: IQ-V-F-N-M-O-W**CONFIGURATION:** IQ MODEL-48VDC-LTGY-N4-SVM-TEMP-1 YEAR

(IQ MODEL WITH 48VDC, LIGHT GRAY FINISH, NEMA TYPE 4, SURFACE VERTICAL MOUNT, FULL SCALE ENCLOSURE CUTOUT DRAWING TEMPLATE, AND 1 YEAR EXTENDED WARRANTY).

PART NUMBER KEY	
IQ	IQ MODEL
V	VOLTAGE
F	FINISH
N	NEMA TYPE
M	MOUNTING
O	OPTIONS
W	WARRANTY
(V) VOLTAGE	
48VDC	
(F) FINISH _{1,5}	
LTGY	LIGHT GRAY, POWDER COATED COLD ROLLED STEEL
S304	GRAINED FINISH, 304 STAINLESS STEEL
S316	GRAINED FINISH, 316 STAINLESS STEEL
(N) NEMA TYPE	
N4	NEMA TYPE 3R/4/12; ONLY FOR UNITS WITH A UNIT CONSTRUCTION OF WELDED FRAME, POWDER COATED COLD ROLLED STEEL.
N4X	NEMA TYPE 3R/4X; ONLY FOR UNITS WITH UNIT CONSTRUCTION OF WELDED FRAME, 304 AND 316L STAINLESS STEEL.
UNIT CONSTRUCTION ₂	
	WELDED FRAME, POWDER COATED COLD ROLLED STEEL
	WELDED FRAME, 304 AND 316L STAINLESS STEEL
(M) MOUNTING ₁	
SVM	SURFACE VERTICAL MOUNT
IVM	INSET VERTICAL MOUNT

(O) OPTIONS _{3,4}	
CP3	HARSH ENVIRONMENT PROTECTION AGAINST GAS, SALT SPRAY, AND MOISTURE. HIGH FREQUENCY COATED COILS, ALL BRAZED JOINTS AND COPPER TUBING COATED.
TEMP	FULL SCALE ENCLOSURE CUTOUT DRAWING TEMPLATE.
XO3	ALARM OUTPUT THAT PROVIDES BOTH A NORMALLY OPEN (CLOSED ON ALARM) AND A NORMALLY CLOSED (OPEN ON ALARM) SET OF DRY CONTACTS. THIS SIGNAL IS PROVIDED FROM A RELAY THROUGH A 3-CONDUCTOR CABLE.
CSU	CUSTOMER SPECIFIC UNIT.
ETHR	ETHERNET CONTROLLER MOUNTED ON UNIT / AC.
(W) WARRANTY ₁	
6 MONTHS	PARTS ONLY
1 YEAR	EXTENDED WARRANTY
2 YEAR	EXTENDED WARRANTY

FOOTNOTES

1. Must choose one from category.
2. Unit construction is paired to finish and NEMA Type.
3. Internal heat is a standard feature. The internal heat will range from 500W to 1000W, dependent on models.
4. Model specific.
5. Light Gray is the standard color; any other color choices are considered optional.
6. The SNMP controller serves as the standard.